

## NAME

texlinks – maintain symbolic links from format to engine

## SYNOPSIS

**texlinks** [ *OPTIONS...* ] *DIRECTORIES...*

## DESCRIPTION

**texlinks** is used to create or recreate symbolic links from formats to engines according to the information in *fmtutil.cnf* or a file specified with **--cnffile**.

*DIRECTORIES* is an optional list of directories in which to operate. If no directories are specified the list of directories depends on the **--multiplatform** option.

## OPTIONS

**--cnffile** *FILE* or **-f** *FILE*

use file as configuration file (default: *fmtutil.cnf*)

**--help** or **-h**

show some help text

**--multiplatform** or **-m**

operate in all platform-specific directories (default: operate only in the directory for this platform)

**--silent** or **-s**

silently skip over existing scripts/binaries instead of printing a warning

**--unlink** or **-u**

Unlink previously created symlinks

**--verbose** or **-v**

+set verbose mode on (default: off)

## FILES

*fmtutil.cnf*

default configuration file

## SEE ALSO

**fmtutil**(1), **fmtutil.cnf**(5)

Web page: <<http://tug.org/teTeX/>>

## BUGS

None known, but report any bugs found to <[tex-k@tug.org](mailto:tex-k@tug.org)> (mailing list).

## AUTHOR

**texlinks** was written by Thomas Esser <[te@dbz.uni-hannover.de](mailto:te@dbz.uni-hannover.de)> in 1999. **texlinks** has been released into the public domain.

This manual page was written by C.M. Connelly <[c@eskimo.com](mailto:c@eskimo.com)>, for the Debian GNU/Linux system. It may be used by other distributions without contacting the author. Any mistakes or omissions in the manual page are my fault; inquiries about or corrections to this manual page should be directed to me (and not to the primary author).